

Breathers: Non-Desiccant (ND-2)

Prevent contamination when humidity is not an issue



Applications:

- Oil sight glasses
- Small gearboxes



ESCO PRODUCTS, INC.

The Overview

Non-Desiccant Breathers: The Highlights


- Filter element captures particles down to 0.3-micron absolute ($\beta_{0.3} \geq 1000$)
- O-ring seal with pipe threading eliminates the need for additional sealant
- Durable nylon 6/6 body
- Filter creates impenetrable barrier against water droplets
- Provides longer oil life
- Reduces wear and tear on equipment, prolongs life

Dimensions & Connections:

Product Specifications	DC-ND-2
Unit Height	1.4"/3.4cm
Unit Diameter	1.8"/4.6cm
Shipping Weight per Unit	0.06lbs./0.03kg
Amount of Desiccant	n/a
Max. Adsorption Capacity (fl oz./ml)	n/a
Max. Air Flow Rate (cfm)	0.67 @ 1psid
Max. Fluid Flow Rate (lpm/gpm)	19/5.02
Filtration	0.3 μ absolute ($\beta_{0.3} \geq 1000$)
Operating Temp. Range	-40°F-300°F/ -40°C-149°C
Hydrophilic Agent	n/a
Filter Media	ePTFE
Connection Size	3/8"
Body Material	Nylon 6/6 (33% glass-filled)

How It Works

As wet, contaminated air is drawn through the unit, the hydrophobic media repels water while the particulate filter captures dirt, preventing both from entering the equipment.



By the Numbers

1-Rugged Exterior

Durable, shock-absorbing housing

2-Threaded Mounting

Easily replaces standard filler/breather cap with adapter/reducer options

3-Hydrophobic Filter Element

Particulate filter element repels water and protects against dirt



ESCO PRODUCTS, INC.

5325 Glenmont Dr. Suite D Houston, TX 77081
800.966.5514 www.esco-inc.com